

Product Information 01.20.64

19-04-2024

Agri Diesel MSP 15W-40

Description

AgriDiesel MSP 15W-40 is a premium, mineral motor oil specially developed for the latest generation of heavy-duty diesel engines in tractors and earth-moving machinery. Special Mid SAPS additive technology, combined with top-quality base oils, ensures that this product provides the following benefits:

- A low sulfate ash, phosphorus and sulfur content, which makes this product suitable for use in engines fitted with an exhaust gas after-treatment device
- Excellent cleaning ability, as a result of which deposits, sludge and particle formation are kept to a minimum
- Superb protection against wear
- Excellent resistance to oxidation and corrosion

Application

AgriDiesel MSP 15W-40 is a high-grade Mid SAPS motor oil suitable for use in the latest generation of diesel engines in agricultural vehicles and earth-moving machinery. Particularly suitable for use in clean Tier IIb and Tier IIIa engines, whether or not equipped with an exhaust gas after-treatment device (particulate filter and/or SCR catalytic converter) and/or an EGR system. If the manufacturer so specifies, longer oil change intervals may be applied.

Specifications

ACEA E7, E9, E11

API CK-4 / SN

Mack EOS-4.5

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

Deutz DQC III-18 LA

DTFR 15C100

Ford WSS M2C171-F1

JASO DH-2

MAN M 3775

MB 228.31

MTU Type 2.1

Allison TES-439

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,877
Viscosity -20 °C, mPa.s	5400
Viscosity 40 °C, mm ² /s	108,00
Viscosity 100 °C, mm ² /s	14,30
Viscosity Index	135
Flash Point COC, °C	240
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,99

Available packagings



35081
5 L can



37495
15 L Bag in
Box



32721
20 L Bag in
Box



34969
20 L pail



34970
60 L drum



34971
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.