



## Product Information 02.35.42

20-04-2024

### Kroon-Oil SP Matic 2034

#### Description

SP Matic 2034 is a premium-quality, extremely low-viscosity Long Life ATF, specifically designed for the latest generation of automatic 8HP transmissions produced by the transmission manufacturer ZF. Specially selected, premium-quality base oils, combined with the latest additives, provide SP Matic 2034 with the following properties:

- Outstanding fuel-saving properties
- Extremely high resistance to oxidation
- Excellent and very stable friction characteristics that enable longer oil-replacement intervals
- Outstanding lubrication properties
- Excellent protection against corrosion and resistance to foaming
- Excellent properties at low temperatures
- Fully compatible with the seal agents used by ZF

#### Application

SP Matic 2034 is a premium synthetic ATF, specially formulated for the latest generation of ZF 8HP transmissions. Compared to ZF 6HP transmissions, even more emphasis is put on fuel saving in the new ZF 8HP transmissions. The very low-viscosity SP Matic 2034 contributes greatly to realising this fuel saving. Among others, the product can be used in these 8HP-Series ZF transmissions: 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions found in various VAG models.

#### Specifications

BMW 8322 2152426/2289720(ATF3+)

Chrysler 68157995AA

Fiat 9.55550-AV5

Jaguar 02JDE 26444

Land Rover LR023288

VW G 060 162

#### Typicals

Colour	GREEN
Density at 15 °C, kg/l	0,849
Viscosity 40 °C, mm <sup>2</sup> /s	27,60
Viscosity 100 °C, mm <sup>2</sup> /s	5,90
Viscosity Index	167
Flash Point COC, °C	208
Pour Point, °C	-51
Total Base Number, mgKOH/g	2,7

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**35649  
1 L bottle36751  
5 L can32764  
20 L Bag in  
Box35651  
20 L pail35652  
60 L drum35898  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.