Product Information 01.40.97

25-04-2024

Kroon-Oil Avanza MSP 0W-30

Description

Avanza MSP 0W-30 is a modern, fuel-saving, fully synthetic motor oil, developed in accordance with the latest Mid SAPS technologies for use in cars with particulate filters and/or catalytic converters. It is supplemented with specially selected, synthetic base oils and advanced additives to achieve the following properties:

- Fuel saving
- Reduced formation of combustion residues due to lower SAPS content
- Extended service life of particulate filters and catalytic converters
- A smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Avanza MSP 0W-30 has been specially developed for modern petrol and diesel engines in cars and vans with a particulate filter and/or catalytic converter. The special Mid SAPS formula extends the service life of those components. If the manufacturer so requires, extended oil change intervals are possible. Suitable for use in the latest PSA models equipped with a particulate filter and for all other makes of car that require an ACEA C2 specification.

Specifications

ACEA C2
API SP
PSA B71 2312
PSA B71 2302
Fiat 9.55535-GS1 / DS1

Typicals

Density at 15 °C, kg/l	0,849
Viscosity -35 °C, mPa.s	6030
Viscosity 40 °C, mm²/s	51,80
Viscosity 100 °C, mm²/s	9,90
Viscosity Index	180
Flash Point COC, °C	220
Pour Point, °C	-48
Total Base Number, mgKOH/g	11,2
Sulphate Ash, %	0,75
HTHS, mPa.s	2,95
Noack, %	12,1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

35941 1 L bottle	36862 5 L can	35942 5 L can	37461 15 L Bag in Box	32899 20 L Bag in Box	35943 20 L pail	35944 60 L drum	35945 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com