

Product Information 09.10.11

04-06-2023

Kroon-Oil Antifreeze SP 11

Description

Antifreeze SP 11 is a premium, Long Life antifreeze for which a patented, nitrite-, amine- and phosphate-free technology with very powerful corrosion inhibitors has been used. With this technology, Antifreeze SP 11 provides longer lasting protection against corrosion than standard antifreeze, so that vulnerable parts such as radiators, water pumps and seals will have a longer service life. Special additives prevent sludge and deposits forming in the radiator, ensuring optimal cooling, even in the long term. Antifreeze SP 11 is specifically designed for use in engines/radiators made from light metals such as aluminium, magnesium or their alloys.

Application

Antifreeze SP 11 is a blue/green, antifreeze for use in a range of models from Mercedes, BMW, Opel and Saab and in a range of models from the VAG group (VW/Audi/Porsche/Seat/Skoda) that require G11 quality. By using powerful corrosion inhibitors, Antifreeze SP 11 is practically unaffected by ageing, giving it a much longer service life than conventional antifreeze. Dilute with demineralised water to the recommended ratio before use.

Specifications

MAN 324-NF

MB 325.0

Opel/GM QL 130100

Porsche/Audi/Seat/Skoda TL-774C (G11)

BMW N 600 69.0

Saab/GM 6901 599

Typicals

Density at 15 °C, kg/l	1,113
Crystallizationpoint: 25 vol%, °C	-12
Crystallizationpoint: 33 vol%, °C	-22
Crystallizationpoint: 40 vol%, °C	-27
Crystallizationpoint: 50 vol%, °C	-40
Crystallizationpoint: 60 vol%, °C	-56

Available packagings



35968
1 L bottle



32954
5 L can



36142
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.