



Product Information 01.20.60

26-04-2024

Dieselfleet CD+ 15W-40

Description

Dieselfleet CD+ 15W-40 is a motor oil for the latest generation of diesel engines, based on premium solvent-refined base oils, supplemented with carefully balanced additives. Dieselfleet CD+ 15W-40 features the following properties:

- Very powerful detergency, thereby reducing deposits in the hot zone of the engine to a minimum
- Very powerful dispersion, which acts to prevent formation of sediment and sludge
- Very resistant to corrosion and foaming
- A high and stable viscosity index
- A low ash content
- Highly effective against wear, resulting in reduced wear of piston rings and cylinder wall

Application

Dieselfleet CD+ 15W-40 is a motor oil suitable for diesel engines both with and without turbochargers, that are used under the most severe operating conditions in all seasons. Dieselfleet CD+ 15W-40 has a high 'Total Base Number' and is thus also suitable for use with fuels with a relatively high sulfur content. This motor oil has been specially developed to facilitate long oil change intervals (45,000 km) and to prevent 'Bore Polishing' (cylinder wall wear).

Specifications

ACEA E7

API CI-4 / SL

DTFR 15B110 (228.3)

Mack EO-N, Renault VI RLD-2

Volvo VDS-3

Cat ECF-1-a / ECF-2

Cummins CES 20077 / 20078

Detroit Diesel 93K215

Deutz DQC III-18

Global DHD-1

JASO DH-1

Mack EO-M Plus

MAN M 3275-1

MB 228.3

MTU Type 2

Allison C3, CAT TO-2












ZF 04C / 04P / 07C / 07D / 21K

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,875
Viscosity -20 °C, mPa.s	6300
Viscosity 40 °C, mm ² /s	115,00
Viscosity 100 °C, mm ² /s	15,10
Viscosity Index	136
Flash Point COC, °C	230
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Acid number, mgKOH/g	4,33
Sulphate Ash, %	1,43

Available packagings

								
35442 1 L bottle	35439 4 L can	31320 5 L can	37518 15 L Bag in Box	32713 20 L Bag in Box	35034 20 L pail	31052 20 L can	10122 60 L drum	31324 200 L drum
								
10222 208 L drum	31036 1000 L IBC							

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.