



Product Information 01.40.60

28-01-2023

Asyntho 5W-30

Description

Asyntho 5W-30 is a modern, universal, fuel-saving, Long Life motor oil based on synthetic base oils with a naturally high viscosity index. It is supplemented with advanced additives to achieve the following properties:

- Fuel saving
- Limited evaporation losses
- A very high 'natural' viscosity index
- Significant resistance to shearing
- Smooth and effective lubrication on cold starts
- Protective lubricant film, even at extremely high operating temperatures
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Asyntho 5W-30 is a synthetic motor oil suitable for petrol and diesel engines, with and without turbochargers, in cars and vans insofar as they require the following specifications.

Specifications

API SN/CF

ACEA A3/B4

BMW Longlife-01

MB 229.3/226.5

Renault RN0700

VW 502.00/505.00

GM LL-A-025/LL-B-025

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	5870
Viscosity 40 °C, mm ² /s	72,8
Viscosity 100 °C, mm ² /s	12,15
Viscosity Index	162
Flash Point COC, °C	251
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Acid number, mgKOH/g	2,10
Sulphate Ash, %	1,32

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



31070
1 L bottle



20029
5 L can



32724
20 L Bag in
Box



45030
20 L pail



20031
60 L drum



20032
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.