

Product Information VM.10.18

01-10-2022

SynTruck Ultimate 5W-30

Description

SynTruck Ultimate 5W-30 is a fuel saving 'Low-SAPS' lubricant with the following properties:

- Very powerful detergency, minimizing deposits in the hot zone of the engine
- Very strong dispersion that restricts the formation of particles to a minimum
- High and stable natural viscosity index
- Low sulphated ash, phosphor and sulphur content ('Low-SAPS')
- Powerful resistance against wear, resulting in strongly reduced wear of piston rings and cylinder-liners
- Lower fuel consumption

Application

SynTruck Ultimate 5W-30 is suitable for EGR engines with or without DPF(diesel particulate filter). This 'Low-SAPS' lubricant is recommended for Euro 4, Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. The product can be used under the toughest operating conditions all year round. Always check the product recommendation database for the right application.

Specifications

ACEA E6, E7, E9, E11

API CK-4/SN

MAN M 3677

MB 228.31/228.51

Mack EO-O Premium Plus

MB-Approval 228.31 / 228.51

Renault VI RLD-3

Scania LDF-4

Volvo VDS-4

Cat ECF-3, Cummins CES 20081

Detroit Diesel 93K218, Deutz DQC IV-10 LA

JASO DH-2, Mack EO-N / EO-M Plus

MAN M 3477 / M 3271-1

MB 235.28

MTU Type 3.1

Scania Low Ash, Renault VI RLD-2 / RXD / RGD

Voith Class B

Volvo VDS-3 / CNG

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6460
Viscosity 40 °C, mm ² /s	70,20
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	165
Flash Point COC, °C	214
Pour Point, °C	-45
Total Base Number, mgKOH/g	9,3
Sulphate Ash, %	0,99
HTHS, mPa.s	3,54
Noack, %	11,7

Available packagings50481
20 L can50482
60 L drum50483
210 L drum