



## Product Information 02.50.14

05-12-2022

### Kroon-Oil SP Matic 4036

#### Description

SP Matic 4036 is a low-viscosity, synthetic Multi ATF. The product has been specially developed for use in modern, fuel-saving, automatic transmissions. New generation additives and advanced, synthetic, low-viscosity base oils provide the following properties:

- Excellent oxidation stability: extending the service life of the fluid
- Outstanding lubrication properties, even under the most extreme conditions
- Very high resistance to wear, corrosion and foaming
- Excellent shear stability
- An extremely low pour point: can be used at extremely low temperatures
- A very high viscosity index: reliable operation of the transmission at both high and low temperatures
- Excellent fuel-saving properties

#### Application

SP Matic 4036 is a synthetic, multi-functional ATF fluid with fuel-saving properties. This product has been specially developed for modern, automatic transmissions by various car manufacturers that require a high-grade, low-viscosity ATF with fuel-saving properties. Consult the advice database for tailor-made product advice.

#### Specifications

Aisin Warner JWS 3324 / AW-1

Ford Mercon LV, Mercon SP

GM Dexron VI

Honda ATF DW-1

Hyundai / Kia SP-IV, SP-IV M, SP-IV RR, SPH-IV

Mazda FZ

Mercedes MB 236.41

Nissan Matic K, Matic S, Matic W

Toyota / Lexus ATF WS

Tesla ATF9 / EDF2

VW G 053 001 / G 053 025 / G 055 005 / G 055 025

VW G 055 162 / G 055 540 / G 060 162

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

## Typicals

Colour	RED
Density at 15 °C, kg/l	0,845
Viscosity 40 °C, mm <sup>2</sup> /s	29,60
Viscosity 100 °C, mm <sup>2</sup> /s	5,90
Viscosity Index	149
Flash Point COC, °C	212
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,7
Acid number, mgKOH/g	1,10
Brookfield -40°C, mPa.s	13000

## Available packagings



32224  
1 L bottle



36750  
5 L can



32225  
15 L Bag in  
Box



32768  
20 L Bag in  
Box



32226  
20 L pail



32227  
60 L drum



32228  
208 L drum