

Product Information 09.10.0424-04-2024

Kroon-Oil Coolant SP 11

Description

Coolant SP 11 is a premium, ready-to-use Long Life coolant (frost protection -37 °C) for which a patented, nitrite-, amine- and phosphate-free technology with very powerful corrosion inhibitors has been used. With this technology, Coolant SP 11 provides longer lasting protection against corrosion than standard antifreeze, so that vulnerable parts such as radiators, water pumps and seals will have a longer service life. Special additives prevent sludge and deposits forming in the radiator, ensuring optimal cooling, even in the long term. Coolant SP 11 is specifically designed for use in engines/radiators made from light metals such as aluminium, magnesium or their alloys.

Application

Coolant SP 11 is a blue/green, ready-to-use coolant for use in a range of models from Mercedes, BMW, Opel and Saab and in a range of models from the VAG group (VW/Audi/Porsche/Seat/Skoda) that require G11 quality. By using powerful corrosion inhibitors, Coolant SP 11 is practically unaffected by ageing, giving it a much longer service life than conventional coolants. Optimal results can only be achieved with a 100% filling.

Specifications

BMW N 600 69.

ASTM D3306 DTFR 29D100

MAN 324-NF

MB 326.0

Opel/GM QL 130100

Porsche/Audi/Seat/Skoda TL-774C (G11)

Saab/GM 6901 599

Typicals

Density at 15 °C, kg/l	1,077
pH - value	7,6

Available packagings



31216

1 L bottle



31217

5 L can









31239 20 L can

31240 60 L drum

31241 208 L drum

32622 1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.