

Product Information 09.10.06

05-05-2024

Kroon-Oil Coolant SP 15

Description

Coolant SP 15 is a premium, ready-to-use Long Life coolant (frost protection down to -38 °C) for which a patented, silicate-free technology based upon carboxyl acids, has been used. With this technology, Coolant SP 15 provides longer lasting protection against corrosion than standard antifreeze, so that vulnerable parts such as radiators, water pumps and seals will have a longer service life.

Powerful corrosion inhibitors prevent sludge and deposits forming in the radiator, ensuring optimal cooling, even in the long term. Coolant SP 15 is specifically designed for use in engines/radiators made from light metals such as aluminium, magnesium or their alloys.

Application

Coolant SP 15 is a fluorescent orange, ready-to-use coolant for the cooling systems in the latest models from the GM group (Opel/Saab/Vauxhall) that require a Long Life coolant with the GM 19 40 650 quality. By using powerful corrosion inhibitors, Coolant SP 15 is practically unaffected by ageing, giving it a much longer service life than conventional coolants. Optimal results can only be achieved with 100% filling.

Specifications

Opel/GM 19 40 650

Saab/GM 19 40 650

Vauxhall/GM 19 40 650

GM 6277M

Typicals

Density at 15 °C, kg/l 1,071

pH - value 8,4

Available packagings



31220
1 L bottle



31221
5 L can



31245
20 L can



31246
60 L drum



31247
208 L drum



34670
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.