

## Product Information PW.40.13

17-05-2025

### Putoline Hydraulic Clutch Fluid

#### Description

Hydraulic Clutch Fluid is a mineral clutch fluid. It protects against wear and oxidation. Hydraulic Clutch Fluid is suitable for Magura and other makes.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

DIN 51524-3 HVLDP

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,850 |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 10,00 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 3,08  |
| Viscosity Index                      | 192   |
| Flash Point COC, °C                  | 144   |
| Pour Point, °C                       | -66   |
| Brookfield -40°C, mPa.s              | 1940  |

#### Available packagings



74209

125 ml pouch



74646

15 L Bag in  
Box