

Product Information PW.40.13

20-04-2024

Putoline Hydraulic Clutch Fluid

Description

Hydraulic Clutch Fluid is a mineral clutch fluid. It protects against wear and oxidation. Hydraulic Clutch Fluid is suitable for Magura and other makes.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

DIN 51524-3 HVLPD

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,850 |
| Viscosity 40 °C, mm ² /s | 10,00 |
| Viscosity 100 °C, mm ² /s | 3,08 |
| Viscosity Index | 192 |
| Flash Point COC, °C | 144 |
| Pour Point, °C | -66 |
| Brookfield -40°C, mPa.s | 1940 |

Available packagings



74209

125 ml pouch

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.