Product Information 01.40.98

12-10-2024

Duranza MSP 0W-30

Description

Duranza MSP 0W-30 is a modern, fuel-saving, synthetic motor oil for use in cars with a particulate filter and/or catalytic converter. The product has been developed in accordance with the most up-to-date advanced additives techniques in combination with selected synthetic base oils. Duranza MSP 0W-30 features the following properties:

- Fuel saving
- Reduced formation of combustion residues due to lower SAPS content
- Extended service life of particulate filters and catalytic converters
- A very smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Duranza MSP 0W-30 is a fuel-saving, synthetic motor oil for the latest generation of cars with a particulate filter and/or catalytic converter. The product is also highly suitable for the latest generation of Ford cars and vans equipped with modern three-way catalytic converters and particulate filters. It can be used whenever Ford specification WSS-M2C950-A is prescribed and in all cases when car manufacturers prescribe the ACEA C2 specification.

Specifications

ACEA C2
Ford WSS-M2C950-A
Jaguar Land Rover STJLR.03.5007
VW VWC 53035

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -35 °C, mPa.s	5800
Viscosity 40 °C, mm²/s	49,30
Viscosity 100 °C, mm²/s	10,00
Viscosity Index	195
Flash Point PM, °C	206
Flash Point COC, °C	230
Pour Point, °C	-48
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,80

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

32382	32383	36488	32384	32385	32386
1 L bottle	5 L can	20 L Bag in Box	20 L pail	60 L drum	208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com