

## Product Information 01.30.81

08-05-2024

### Kroon-Oil Torsynth MSP 5W-30

#### Description

Torsynth MSP 5W-30 is a synthetic Mid-SAPS motor oil that has been specially developed for modern cars and vans with a particulate filter and/or new generation 3-way catalytic converter. This product's performance level is entirely in line with the officially approved product. Because the necessary field testing has not been conducted for Torsynth MSP 5W-30 we can only say that the product meets the requirements of the specified performance levels.

#### Application

Torsynth MSP 5W-30 is a Mid-SAPS motor oil, suitable for modern petrol, LPG and diesel engines that are no longer covered by a manufacturer's warranty. This product is also suitable for extended oil change intervals. Due to its low SAPS content this oil is also suitable for vehicles with a particulate filter and/or latest generation 3-way catalytic converter. As a result of its special formulation this product is ideal for use in cars requiring one of the following specifications.

#### Specifications

Suitable for use:

ACEA C2, C3

API SN

BMW Longlife-04

GM dexos 2

MB 229.51 / 229.52

Opel OV 040 1547 - D30

VW 505.01

#### Typicals

Density at 15 °C, kg/l 0,855

Viscosity -30 °C, mPa.s 6000

Viscosity 40 °C, mm<sup>2</sup>/s 73,00

Viscosity 100 °C, mm<sup>2</sup>/s 12,10

Viscosity Index 163

Flash Point COC, °C 230

Pour Point, °C -36

Total Base Number, mgKOH/g 7,8

Sulphate Ash, % 0,77

#### Available packagings



32644  
1 L bottle



37151  
4 L can



32645  
5 L can



37486  
15 L Bag in  
Box



32638  
20 L Bag in  
Box



32461  
20 L pail



32388  
60 L drum



32389  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.