



Product Information 01.20.61

20-04-2024

Dieselfleet CD+ (TBN 16) 15W-40

Description

Dieselfleet CD+ (TBN 16) 15W-40 is one of the latest generation of motor oils for diesel engines, based on premium solvent-refined base oils, supplemented with carefully balanced additives. Dieselfleet CD+ (TBN 16) 15W-40 features the following properties:

- Very powerful detergency, thereby reducing deposits in the hot zone of the engine to a minimum
- Very powerful dispersion, which acts to minimise formation of sediment and sludge
- Very high resistance to corrosion and foaming
- A high and stable viscosity index
- A low sulphate ash content
- High wear resistance resulting in significantly reduced wear of piston rings and cylinder wall

Application

Dieselfleet CD+ (TBN 16) 15W-40 is a motor oil suitable for diesel engines, both with and without turbochargers, that are used under the most severe operating conditions in all seasons. The product has a high TBN, making it suitable for use with fuels with a relatively high sulphur content. This motor oil has been specially developed in order to allow long oil change intervals (45,000 km) and to prevent 'Bore Polishing' (= wear of the cylinder wall).

Specifications

ACEA E7

API CI-4 / SL

Cat ECF-1-a / ECF-2

Cummins CES 20077/20078

Detroit Diesel 93K215

Deutz DQC III-18

DTFR 15B110

Global DHD-1

JASO DH-1

Mack EO-N/EO-M Plus

MAN M 3275-1

MB 228.3

MTU Type 2

Renault VI RLD-2

Volvo VDS-3

Allison C3, CAT TO-2

ZF 04C / 04P / 07C / 07D / 21K

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,886
Viscosity -20 °C, mPa.s	6300
Viscosity 40 °C, mm ² /s	110,30
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	135
Flash Point COC, °C	212
Pour Point, °C	-30
Total Base Number, mgKOH/g	16,1
Sulphate Ash, %	2,00

Available packagings



32239
5 L can



45055
20 L pail



20056
60 L drum



32474
200 L drum



20057
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.