

Product Information VM.40.05

30-01-2023

Motorcycle 4T FS 10W-40

Description

Motorcycle 4T FS 10W-40 is a fully synthetic, superior performance 4-stroke competition engine oil. High-grade base oils guarantee outstanding performance in the following areas, among others: - A very powerful lubricating film, even under the most extreme operating conditions - Maximum engine performance - A very high and extremely stable viscosity index - Optimal functioning of the wet clutch - Accurate and smooth gear-changing - Superior protection against wear - Minimum oil consumption as a result of low volatility
Motorcycle 4T FS 10W-40 has been exclusively developed for modern, high-tech, high to very high performance race and road motorcycles.

Application

Motorcycle 4T FS 10W-40 has been developed specifically for modern, high-tech, high to very high-powered motorcycles. This fully synthetic formula means that the product offers superior lubrication, even under extremely high operating temperatures. This makes Motorcycle 4T FS 10W-40 particularly suitable for use in sports and on the circuit, as well as when riding on normal roads.

Specifications

API SL

JASO MA2

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -25 °C, mPa.s	3370
Viscosity 40 °C, mm ² /s	83,6
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	163
Flash Point COC, °C	236
Pour Point, °C	-33
Total Base Number, mgKOH/g	7,6

Available packagings



50503
1 L bottle



50504
4 L can



50579
20 L can



50571
60 L drum



50572
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.