

Product Information 01.30.11

29-04-2024

Emperol Diesel 10W-40

Description

Emperol Diesel 10W-40 is a modern, fuel-saving, diesel motor oil. The product is based on mineral and synthetic base oils that have a naturally high viscosity index. It is supplemented with carefully balanced additives to achieve the following properties:

- Fuel saving: up to 2 %
- Extremely high viscosity index and high resistance to shearing
- A smooth cold start
- A protective lubricant film at high temperatures
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming
- Effective resistance to certain features that are typical of diesel engines, such as the thickening of oil during use

Application

Emperol Diesel 10W-40 is a specific diesel motor oil, suitable for all diesel engines, both with and without turbochargers. Consult the product advice database for optimal use.

Specifications

Suitable for use:

API SL/CF

ACEA A3/B4

BMW Longlife-98

MB 229.1

VW 501.01/505.00

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,872 |
| Viscosity -25 °C, mPa.s | 4100 |
| Viscosity 40 °C, mm ² /s | 89,90 |
| Viscosity 100 °C, mm ² /s | 14,00 |
| Viscosity Index | 160 |
| Flash Point COC, °C | 232 |
| Pour Point, °C | -39 |
| Total Base Number, mgKOH/g | 11,4 |
| Sulphate Ash, % | 1,31 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



34468
1 L bottle



35654
4 L can



31328
5 L can



37526
15 L Bag in
Box



32714
20 L Bag in
Box



34469
20 L pail



34470
60 L drum



34471
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.