

Product Information 09.30.03

23-04-2024

Kroon-Oil Kroon-O-Sol

Description

Kroon-O-Sol is a mineral emulsifiable degreaser, based on a highly refined solvent. Selected substances have been added in order to achieve a good cleaning effect. Kroon-O-Sol removes oils, greases, dirt and other impurities from components, engines, machines, etc.

Kroon-O-Sol is non-aggressive and does not pose a fire risk as it has a high flash point of 70°C.

Application

Apply Kroon-O-Sol to the surface to be cleaned using a brush or spray. After allowing it to soak in for 3 to 5 minutes, the item to be cleaned can be rinsed with running water or a high pressure hose. For smaller items, Kroon-O-Sol can also be used in an immersion process.

NB: Kroon-O-Sol or rinsing water must not be released directly into municipal sewers or surface water. Ensure that the rinsing water is passed through an oil-water separator.

Typicals

| | |
|-------------------------------------|-------|
| Density at 15 °C, kg/l | 0,798 |
| Viscosity 40 °C, mm ² /s | 1,60 |
| Flash Point PM, °C | 72 |
| Pour Point, °C | -36 |
| pH - 10 % in water | 8,0 |

Available packagings



03308
5 L tin



13008
20 L can



13108
60 L drum



13208
208 L drum