

Product Information 01.10.34

27-04-2024

Multifleet SCD 50

Description

Multifleet SCD 50 is a modern, universal motor oil based on premium solvent-refined base oils, supplemented with carefully balanced additives. Multifleet SCD features the following properties:

- Excellent detergency, thereby preventing deposits in the hot zone of the engine
- Excellent dispersion, which acts to prevent the formation of sediment and sludge
- Very high resistance to wear, corrosion and foaming
- A low ash content

Application

Multifleet SCD 50 is a universal, single-grade motor oil suitable for petrol and diesel engines, both with and without turbochargers, under all operating conditions.

Specifications

API SG/CF

MB 227.0/228.0

MAN 270

Typicals

Density at 15 °C, kg/l	0,900
Viscosity 40 °C, mm ² /s	206,00
Viscosity 100 °C, mm ² /s	19,40
Viscosity Index	107
Flash Point COC, °C	236
Pour Point, °C	-15
Total Base Number, mgKOH/g	6,9
Sulphate Ash, %	0,91

Available packagings



37546
15 L Bag in
Box



34312
20 L pail



32634
60 L drum



32586
200 L drum



31169
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.