

## Product Information PM.40.47

24-10-2021

### V -Twin Mineral 20W-50

#### Description

Genuine V-Twin Mineral 20W-50 is a fully mineral engine oil, specially developed for various air- and liquid-cooled V-Twin motorbike engines that have not been fitted with a wet clutch. By using the most up-to-date additive technology, the following properties are achieved:

- Unparalleled low friction values
- Excellent cold-start protection
- Low oil consumption The product is suitable for various V-Twin motorcycles with combined or separate lubrication for the engine, gearbox and primary chaincase for which SAE 20W-50 engine oil is specified.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

API CH-4/SJ

#### Typicals

Density at 15 °C, kg/l	0,897
Viscosity -15 °C, mPa.s	7600
Viscosity 40 °C, mm <sup>2</sup> /s	154,30
Viscosity 100 °C, mm <sup>2</sup> /s	17,30
Viscosity Index	122
Flash Point COC, °C	226
Pour Point, °C	-30
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43
Noack, %	7,7

#### Available packagings



74220  
1 L tin



74305  
60 L drum



74422  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.