

## Product Information 01.30.23

25-04-2024

### Torsynth VAG 5W-30

#### Description

Torsynth VAG 5W-30 is a synthetic Mid-SAPS Long Life motor oil that has been specially developed for VAG cars. This product's performance level is entirely in line with the officially approved product. Because the necessary field testing has not been conducted for Torsynth VAG 5W-30 we can only say that the product meets the requirements of the specified performance levels.

#### Application

Torsynth VAG 5W-30 is a fuel-saving, Mid-SAPS motor oil, suitable for petrol, LPG and diesel engines from the VAG group that are no longer covered by a manufacturer's warranty. Also suitable for extended oil change intervals. Due to its Low SAPS content this oil is also suitable for vehicles with a particulate filter and/or latest generation 3-way catalytic converter. This product is ideal for use in VAG group cars that require a motor oil specification 504.00/ 507.00.

#### Specifications

Suitable for use:

ACEA C3

API SN

BMW Longlife-04

MB 229.31/229.51/229.52

VW 504.00/507.00

#### Typicals

Density at 15 °C, kg/l 0,856

Viscosity -30 °C, mPa.s 5650

Viscosity 40 °C, mm<sup>2</sup>/s 71,60

Viscosity 100 °C, mm<sup>2</sup>/s 12,20

Viscosity Index 168

Flash Point COC, °C 234

Pour Point, °C -39

Total Base Number, mgKOH/g 8,3

Sulphate Ash, % 0,74

Silicon, mg/kg 3

#### Available packagings



32642  
1 L bottle



32643  
5 L can



37464  
15 L Bag in  
Box



32637  
20 L Bag in  
Box



32460  
20 L pail



32147  
60 L drum



32148  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.