

Product Information 01.30.81 27-04-2024

Kroon-Oil Torsynth MSP 5W-30

Description

Torsynth MSP 5W-30 is a synthetic Mid-SAPS motor oil that has been specially developed for modern cars and vans with a particulate filter and/or new generation 3-way catalytic converter. This product's performance level is entirely in line with the officially approved product. Because the necessary field testing has not been conducted for Torsynth MSP 5W-30 we can only say that the product meets the requirements of the specified performance levels.

Application

Torsynth MSP 5W-30 is a Mid-SAPS motor oil, suitable for modern petrol, LPG and diesel engines that are no longer covered by a manufacturer's warranty. This product is also suitable for extended oil change intervals. Due to its low SAPS content this oil is also suitable for vehicles with a particulate filter and/or latest generation 3-way catalytic converter. As a result of its special formulation this product is ideal for use in cars requiring one of the following specifications.

Specifications

Suitable for use:	
ACEA C2, C3	
API SN	
BMW Longlife-04	
GM dexos 2	
MB 229.51 / 229.52	
Opel OV 040 1547 - D30	
VW 505.01	

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6000
Viscosity 40 °C, mm²/s	73,00
Viscosity 100 °C, mm²/s	12,10
Viscosity Index	163
Flash Point COC, °C	230
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77

Available packagings



















32644 1 L bottle

4 L can

5 L can

37486

15 L Bag in Box

20 L Bag in Box

32638

20 L pail

60 L drum

208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification