

## Product Information 01.40.83

17-05-2025

### Expulsa RR 5W-50

#### Description

Expulsa RR 5W-50 is a fully synthetic, superior performance 4-stroke engine oil for the latest generation of motorcycles. Expulsa RR 5W-50 is based on premium synthetic base oils and advanced special additives to achieve the following properties:

- Outstanding protection against wear even at extremely high or low temperatures
- Excellent lubrication under the most extreme operating conditions
- A low volatility, therefore resulting in minimal oil consumption
- Very limited internal friction for maximum engine performance
- A very high and stable viscosity index
- Outstanding cleaning properties, ensuring that the interior of the engine remains clean
- Ensures that gear-changing is both smooth and accurate
- Optimally functioning wet clutch

#### Application

Expulsa RR 5W-50 has been developed specifically for modern, high-tech, high to very high-powered motorcycles. This fully synthetic formula means that Expulsa RR 5W-50 offers superior lubrication, even at extremely high operating temperatures. This makes the product particularly suitable for use in sports and on the circuit, as well as when riding on normal roads.

#### Specifications

API SP

JASO MA2

#### Typicals

Density at 15 °C, kg/l	0,846
Viscosity -30 °C, mPa.s	4440
Viscosity 40 °C, mm <sup>2</sup> /s	114,00
Viscosity 100 °C, mm <sup>2</sup> /s	18,00
Viscosity Index	176
Flash Point COC, °C	226
Pour Point, °C	-54
Total Base Number, mgKOH/g	7,1
Sulphate Ash, %	0,82
HTHS, mPa.s	4,49
Noack, %	7,3

#### Available packagings



33017  
1 L bottle



58038  
20 L pail



37950  
20 L can



33039  
60 L drum



32671  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.