

Product Information 01.40.84

20-04-2024

Expulsa RR 15W-50

Description

Expulsa RR 15W-50 is a fully synthetic, superior-performance 4-stroke engine oil for the latest generation of motorcycles. Expulsa RR 15W-50 is based on premium synthetic base oils and advanced special additives to achieve the following properties:

- Outstanding protection against wear even at extremely high or low temperatures
- Excellent lubrication under the most extreme operating conditions
- A low volatility, therefore resulting in minimal oil consumption
- Very limited internal friction for maximum engine performance
- A very high and stable viscosity index
- Outstanding cleaning properties, ensuring that the interior of the engine remains clean
- Ensures that gear-changing is both smooth and accurate
- Optimally functioning wet clutch

Application

Expulsa RR 15W-50 has been developed specifically for modern, high-tech, high to very high-powered motorcycles. This fully synthetic formula means that Expulsa RR 15W-50 offers superior lubrication, even at extremely high operating temperatures. This makes Expulsa RR 15W-50 particularly suitable for use in sports, both on the street and on the circuit.

Specifications

API SN

JASO MA2

Typicals

Density at 15 °C, kg/l	0,845
Viscosity -25 °C, mPa.s	3380
Viscosity -20 °C, mPa.s	2010
Viscosity -15 °C, mPa.s	1360
Viscosity 40 °C, mm ² /s	119,00
Viscosity 100 °C, mm ² /s	18,00
Viscosity Index	168
Flash Point COC, °C	256
Pour Point, °C	-60
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,85

Available packagings



33015
1 L bottle



58042
20 L pail



33043
60 L drum



32673
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.