

Product Information 01.10.35

29-04-2024

Gas Engine Oil Bio-LF 40

Description

Gas Engine Oil Bio-LF 40 is a motor oil for gas engines. Specially developed for the lubrication of 4-stroke gas engines that use biogas and landfill gas with a relatively high degree of contamination. The use of specialist, state-of-the-art, high quality base oils, combined with newly-developed additives, gives the product the following properties:

- Causes fewer deposits in the combustion chamber and on the valves
- Good noise-reduction properties
- Excellent oxidation stability
- Excellent ability to neutralise acids
- Excellent cleaning properties
- Provides good protection against wear
- Excellent filterability

Application

Gas Engine Oil Bio-LF 40 is suitable for use in 4-stroke gas engines that require an oil with a higher acid neutralising capacity. It is especially suitable for vehicles using biogas or landfill gas. The fact that oil change intervals can be longer means that this motor oil helps extend the service life and reduces maintenance costs. Its low phosphorus-content also extends the life of the vehicle's catalytic converter.

Specifications

GE Jenbacher class B (biogas)

GE Jenbacher class C (landfill gas)

GE Jenbacher type 2 and 3 all engine versions

GE Jenbacher type 4 engine versions A and B

GE Jenbacher type 6 engine versions C and E

GE TA 1000-1109

MAN M 3271-4 (Special gas)

MAN M 3271-5 (Special gas)

MWM TR 0199-99-(1)2105

Typicals

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm ² /s	124,40
Viscosity 100 °C, mm ² /s	13,30
Viscosity Index	105
Flash Point COC, °C	270
Pour Point, °C	-21
Total Base Number, mgKOH/g	4,5
Sulphate Ash, %	0,57

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



32675
20 L pail



32283
60 L drum



35714
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.