

Product Information 98.40.03

21-02-2019

Gear Oil Alcat 10W

Description

Gear Oil Alcat 10W is a special oil for hydraulic and transmission applications, based on solvent-refined base oils, supplemented with additives to achieve the following properties:

- A very low pour point
- Excellent oxidation stability
- Good wear resistance, as a result of which the final drives achieve a longer service life
- Special friction properties that ensure optimal use of powershift transmissions
- Suitable for systems with wet brakes
- Outstanding resistance to rust and corrosion

Application

Gear Oil Alcat 10W has been specially developed for the lubrication of powershift transmissions, differentials, final drives and hydraulic systems in earth moving equipment for which oil is recommended that complies with the Caterpillar TO-4 or Allison C4 specifications.

THE OIL CANNOT BE USED IN ENGINES!

Specifications

Allison C4

Cat TO-4/TO-2

Komatsu KES 07.868.1

ZF TE-ML 03C

Typicals

Density at 15 °C, kg/l	0,860
Viscosity 40 °C, mm ² /s	40,50
Viscosity 100 °C, mm ² /s	6,48
Viscosity Index	111
Flash Point COC, °C	226
Pour Point, °C	-30
Sulphate Ash, %	1,32

Available packagings



35771
20 L can



33030
60 L drum



33031
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.