Product Information 02.30.40

12-10-2024

ATF Almirol

Description

ATF Almirol is a premium automatic transmission oil for the latest generation. By selecting premium-quality base oils and optimising the synthetic package of additives, the product features the following unique properties:

- Extremely low viscosity at low temperatures
- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability at high temperatures
- Effective resistance to wear, corrosion and foaming
- Special friction properties
- Does not affect seals and non-ferrous metals

Application

ATF Almirol is suitable for automatic transmissions, power steering systems, torque converters and other applications for which General Motors and other constructors recommend a type ATF Dexron III-H oil. Consult the product specifications in the product sheet for correct usage.

Specifications

Allison C4 / TES-389
Cat TO-2
DTFR 13C100 / 13C140 / 13C170 / 38B100
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID / IIE / IIIF / IIIG / IIIH / TASA
MAN 339 Typ Z1 / V1 / Z2
MB 236.1 / 236.3 / 236.5 / 236.6
MB 236.7 / 236.9 / 236.10 / 236.93
Voith 55.6335 (G607)
Volvo 97340 / 97341 (AT101)
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C
Ford ESD-M2C-186A

Typicals

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm²/s	36,00
Viscosity 100 °C, mm²/s	7,30
Viscosity Index	175
Flash Point COC, °C	226
Pour Point, °C	-48
Total Base Number, mgKOH/g	0,9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

01212 1 L bottle	01322 5 L can	37505 15 L Bag in Box	32740 20 L Bag in Box	36087 20 L pail	35214 20 L can	11175 60 L drum	11275 208 L drum	35107 1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com