



## Product Information 08.10.02

15-04-2024

### Perlus AF 46

#### Description

Perlus AF 46 is a premium 'Extreme Pressure' hydraulic oil, based on specially selected solvent-refined base oils, with a naturally high viscosity index, supplemented with additives to achieve the following properties:

- Outstanding wear resistance
- Excellent resistance to rust and corrosion
- Excellent oxidation stability
- Excellent demulsifier
- Excellent air-release and resistance to foaming
- Does not affect synthetic seals
- A low pour point

#### Application

Perlus AF 46 is suitable both for heavy-duty hydraulic installations and for gear transmissions and bearings subject to light loads. Furthermore, Perlus AF 46 is also highly suitable for use as circulation lubrication (with the exception of turbines), for vacuum pumps and general mechanical lubrication.

#### Specifications

AFNOR NF E 48-603 HM

ASTM D 6158 HM

Cincinnati Machine P-70

Denison HF-0/HF-1/HF-2

DIN 51524-2 HLP

Eaton Brochure 694 for 35VQ25A

GM LS-2

ISO 11158 HM

ISO 6743-3 DVC

#### Typicals

Density at 15 °C, kg/l	0,877
Viscosity 40 °C, mm <sup>2</sup> /s	46,60
Viscosity 100 °C, mm <sup>2</sup> /s	6,76
Viscosity Index	98
Flash Point COC, °C	212
Pour Point, °C	-39
Acid number, mgKOH/g	1,50
Sulphate Ash, %	0,06
Conductivity, pS	124

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**



32749  
20 L Bag in  
Box



37074  
20 L pail



32037  
20 L can



12126  
60 L drum



31398  
200 L drum



12224  
208 L drum



20050  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.