

# **Product Information 02.35.44** 05-05-2024

## **Kroon-Oil SP Matic 2096**

#### **Description**

SP Matic 2096 is a premium-quality, extremely low-viscosity 'Long-Life' ATF, specifically designed for the latest generation of fuel-efficient automatic transmissions. Specially selected, premium-quality base oils, combined with the latest additives, provide SP Matic 2096 with the following properties:

- Outstanding fuel-saving properties
- Extremely high resistance to oxidation
- Excellent and very stable friction characteristics for extended oil change intervals
- Outstanding lubrication properties
- Excellent protection against corrosion and foaming
- Excellent low temperature properties
- Fully compatible with sealing agents used by Mercedes

#### **Application**

SP Matic 2096 is a very high-quality, synthetic ATF, specially developed for the latest generation of automatic transmissions, with a strong emphasis on fuel economy. For such modern fuel-efficient transmissions, new-generation ATFs with ultra-low viscosity are increasingly prescribed by car manufacturers, contributing significantly to lower fuel consumption.

## **Specifications**

Aisin Warner AW-2

	Albin Warrier AW 2
	BMW 83 22 2 413 477 (ATF7)
	Ford Mercon ULV
	Ford M2C949-A
	GM Dexron ULV ATF
	MB 236.17
	VW G053 001

## **Typicals**


Density at 15 °C, kg/l	0,840
Viscosity 40 °C, mm <sup>2</sup> /s	17,10
Viscosity 100 °C, mm²/s	4,23
Viscosity Index	161
Flash Point COC, °C	174
Pour Point, °C	-57
Total Base Number, mgKOH/g	3,4
Acid number, mgKOH/g	1,00

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



## **Available packagings**







32820 1 L bottle



32842 20 L Bag in Box



60 L drum



32844 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.