



Product Information 02.20.50

15-07-2024

SP Gear 1011

Description

SP Gear 1011 is an extremely modern, fully synthetic 75W-90 transmission oil. By using low-viscosity, synthetic base oils and highly advanced technology, the following unique properties are achieved:

- Ensures effective gear-changing in cold or warm conditions
- Ensures fuel saving: up to 2%, cost effective
- Suitable for the entire drive line: Total Drive Line Oil means that fewer individual products are required
- A powerful lubricant film, even under the toughest conditions, for added security
- Effective in preventing wear on gears and bearings and ensures long service life
- Copes exceptionally well with the (long) oil change intervals of today
- Does not affect seals: prevents leakages

Application

SP Gear 1011 is a fuel-saving, fully synthetic transmission oil, suitable for the entire drive line with a premium quality (API: GL5+ level). The product has been developed for use in the most heavy-duty transmissions in manual transmissions, transfer boxes and final drives. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

API GL-3 / GL-4 / GL-5 / MT-1

MIL-L-2105D / MIL-PRF-2105E, SAE J2360

MAN 341 Typ Z2 / 342 Typ S1

DTFR 12B140 (235.8)

Scania STO 1:1 G / 2:0 A FS

ZF TE-ML 02B / 05A / 12L / 12N

ZF TE-ML 16F / 17B / 19C / 21A

Arvin Meritor 076-N

DAF, Iveco

Mack GO-J

MAN 3343 Typ S / 341 Typ E3 / 341 Typ GA1

MB 235.8 / 235.9

Scania STO 1:0

Volvo 97312

Ford WSD-M2C-200B/C

ZF TE-ML 07A / 12B / 16B

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,871
Viscosity 40 °C, mm ² /s	101,00
Viscosity 100 °C, mm ² /s	15,40
Viscosity Index	161
Flash Point COC, °C	202
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,1

Available packagings



02229
1 L bottle



37496
15 L Bag in
Box



32908
20 L Bag in
Box



45016
20 L pail



12184
60 L drum



12285
208 L drum



33184
1000 L IBC