



## Product Information 02.20.50

04-06-2023

### SP Gear 1011

#### Description

SP Gear 1011 is an extremely modern, fully synthetic 75W-90 transmission oil. By using low-viscosity, synthetic base oils and highly advanced technology, the following unique properties are achieved:

- Ensures effective gear-changing in cold or warm conditions
- Ensures fuel saving: up to 2%, cost effective
- Suitable for the entire drive line: Total Drive Line Oil means that fewer individual products are required
- A powerful lubricant film, even under the toughest conditions, for added security
- Effective in preventing wear on gears and bearings and ensures long service life
- Copes exceptionally well with the (long) oil change intervals of today
- Does not affect seals: prevents leakages

#### Application

SP Gear 1011 is a fuel-saving, fully synthetic transmission oil, suitable for the entire drive line with a premium quality (API: GL5+ level). The product has been developed for use in the most heavy-duty transmissions in manual transmissions, transfer boxes and final drives. Always consult the Kroon-Oil advisory database for optimal use.

#### Specifications

API GL-3/GL-4/GL-5/MT-1

MIL-L-2105D / MIL-PRF-2105E, SAE J2360

MB-Approval 235.8

MAN 341 Typ Z2 / 342 Typ S1

Scania STO 1:1 G / 2:0 A FS

ZF TE-ML 02B / 05A / 12L / 12N

ZF TE-ML 16F / 17B / 19C / 21A

Arvin Meritor 076-N

DAF, Iveco

Mack GO-J

Scania STO 1:0

Volvo 97312

ZF TE-ML 07A / 12B / 16B

MAN 3343 Typ S / 341 Typ E3

Ford WSD-M2C-200B/C

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,869
Viscosity 40 °C, mm <sup>2</sup> /s	101,00
Viscosity 100 °C, mm <sup>2</sup> /s	15,40
Viscosity Index	161
Flash Point COC, °C	202
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,1

### Available packagings



02229  
1 L bottle



32908  
20 L Bag in  
Box



45016  
20 L pail



12184  
60 L drum



12285  
208 L drum