

Product Information 02.35.10

04-02-2023

Kroon-Oil SP Matic 2032

Description

SP Matic 2032 is a premium, synthetic Long Life ATF, specially developed for use in automatic transmissions with a continuous slip lock-up converter. The product features the following properties:

- Excellent oxidation stability: lasts longer
- Outstanding lubrication properties: optimal protection
- Excellent resistance to corrosion and foaming: effective protection
- An extremely low pour point can be used at extremely low temperatures
- Does not affect seals used: prevents leakages

Application

SP Matic 2032 can be used for automatic transmissions with a continuous slip lock-up converter and is often used in the automatic transmissions of a large number of well-known car manufacturers. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

Allison C4/TES-389

Cat TO-2

Ford Mercon/M2C138-CJ/166-H

GM Dexron IID/IIE/IIIF/IIIG/IIIH

MAN 339 Typ Z1/V1/Typ Z2/V2

MB 236.1/236.5/236.6/236.7/236.9/236.10

Voith 55.6335/55.6336

Volvo 97340/97341

ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Typicals

Density at 15 °C, kg/l	0,851
Viscosity 40 °C, mm ² /s	34,7
Viscosity 100 °C, mm ² /s	7,40
Viscosity Index	188
Flash Point COC, °C	250
Pour Point, °C	-48
Total Base Number, mgKOH/g	0,9

Available packagings



02230
1 L bottle



35476
15 L Bag in
Box



32763
20 L Bag in
Box



56312
20 L pail



31134
60 L drum



31138
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.