

Product Information 06.20.60

17-05-2025

Fork Oil RR 5

Description

Fork Oil RR 5 is a premium fork oil based on carefully selected base oils and special additives to achieve the following properties:

- A high viscosity index, which ensures constant and reliable handling in any weather
- Excellent air-release and resistance to foaming, which ensures a constant performance level, whatever the operating conditions
- Excellent protection against wear, which ensures a long service life
- Optimal protection against corrosion
- Does not affect synthetic seals
- A low pour point

Application

Fork Oil RR 5 has been specially developed for use in front forks and shock absorbers on motorcycles. Suitable for use in road bikes, off-road motorcycles and motorcycles used for racing.

Typicals

Density at 15 °C, kg/l	0,855
Viscosity 20 °C, mm ² /s	51,30
Viscosity 40 °C, mm ² /s	21,70
Viscosity 100 °C, mm ² /s	5,01
Viscosity Index	168
Flash Point COC, °C	193
Pour Point, °C	-54
Calcium, mg/kg	0
Phosphorus, mg/kg	0
Zinc, mg/kg	0

Available packagings



33131
20 L pail



37956
20 L can



33611
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.