



Product Information 01.40.03

28-01-2023

Poly Tech 5W-40

Description

Poly Tech 5W-40 is a premium motor oil that protects critical engine parts in vehicles operating under extreme conditions. The product is based on high-quality base oils combined with a highly advanced package of additives that includes special 'OSP' additives, among others. Poly Tech 5W-40 features the following properties:

- Vastly improved cleaning properties
- Outstanding shear stability thanks to the high VI of the base oils used
- A very smooth cold start, even at extremely low temperatures, significantly reducing wear on starting
- Delays the ageing process of the engine
- Excellent protection against wear and corrosion
- Improved oxidation stability
- Reduces friction in the moving engine parts
- Minimises oil consumption

Application

Poly Tech 5W-40 is a premium motor oil for use in both petrol and diesel engines in cars and vans. By applying special 'OSP' additives, Poly Tech 5W-40 is ideally suited for use in vehicles exposed to extreme conditions. This may include frequently crawling through heavy traffic, 'sporty' driving or regular cold starts.

Specifications

ACEA A3/B4

API SN/CF

BMW Longlife-01

GM LL-B-025

MB 229.3/226.5

Porsche A40

Renault RN0700/RN0710

VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	4370
Viscosity 40 °C, mm ² /s	82,0
Viscosity 100 °C, mm ² /s	13,80
Viscosity Index	173
Flash Point COC, °C	235
Pour Point, °C	-57
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.