

## Product Information 01.50.16

11-07-2025

### Agrisynt LSP Ultra FE 5W-30

#### Description

Agrisynt LSP Ultra FE 5W-30 is a fuel saving Low-SAPS lubricant with the following properties:

- Very powerful detergency, minimizing deposits in the hot zone of the engine
- Very strong dispersion that restricts the formation of particles to a minimum
- High and stable natural viscosity index
- Low sulphated ash, phosphor and sulphur content (Low-SAPS)
- Powerful resistance against wear, resulting in strongly reduced wear of piston rings and cylinder-liners
- Lower fuel consumption

#### Application

Agrisynt LSP Ultra FE 5W-30 is suitable for EGR engines with or without DPF (diesel particulate filter). This Low-SAPS lubricant is recommended for Euro 4, Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. The product can be used under the toughest operating conditions all year round. Always check the product recommendation database for the right application.

#### Specifications

ACEA E6, E7, E8, E9, E11

API CK-4 / SN

Deutz DQC IV-18 LA

Mack EOS-4.5

MAN M 3677

DTFR 15C110 (228.51)

Renault VI RLD-3

Scania LDF-4

Volvo VDS-4.5

DAF PSQL 2.4 LD / 2.1E LD

Cat ECF-3, Cummins CES 20086

Detroit Diesel DFS 93K222

DTFR 15C120 / 15C100

Ford WSS-M2C213-A1, JASO DH-2

MAN M 3775 / M 3271-1 / M 3477

MB 228.51

MB 228.51 / 228.52 / 228.31

MTU Type 3.1, Scania Low Ash

DAF Extended Drain, Iveco 18-1804 TLS E9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	6120
Viscosity 40 °C, mm <sup>2</sup> /s	75,10
Viscosity 100 °C, mm <sup>2</sup> /s	12,00
Viscosity Index	156
Flash Point COC, °C	222
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,8
Sulphate Ash, %	0,97
HTHS, mPa.s	3,57
Noack, %	10,7

### Available packagings



37761  
15 L Bag-in-  
Box



37935  
20 L can



36181  
60 L drum



36182  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.