

Product Information 01.10.10

18-04-2024

Motor Oil Regular 30

Description

Motor Oil Regular 30 is a premium, solvent-refined motor oil with outstanding resistance to ageing and with a high viscosity index. Furthermore, it is supplemented with additives that act against oxidation and corrosion.

Application

Motor Oil Regular 30 is suitable for systems in which the oil is not under a heavy load, such as bearings in pumping engines, transmissions subjected to light loads and circulation lubrication systems.

Specifications

API SA

Typicals

Density at 15 °C, kg/l	0,893
Viscosity 40 °C, mm ² /s	102,00
Viscosity 100 °C, mm ² /s	11,50
Viscosity Index	98
Flash Point COC, °C	244
Pour Point, °C	-18

Available packagings



33167
20 L pail



10103
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.