

Product Information VC.10.04

29-01-2023

VatOil Antifreeze LL 12

Description

Antifreeze LL 12 is a premium, lilac-coloured, organic Long Life antifreeze. Thanks to the use of the very latest OAT corrosion inhibitors, Antifreeze LL 12 provides much longer lasting protection against corrosion than standard antifreeze, so that vulnerable parts such as radiators, water pumps and seals will have a longer service life.

Application

Antifreeze LL 12 has been specially developed for cooling systems made from light metals, such as aluminium, magnesium and/or their alloys. It can be used safely in conventional cast-iron cooling systems. Powerful corrosion inhibitors mean that it is practically unaffected by ageing, giving it a much longer service life compared with that of conventional antifreeze products. An optimal result can only be attained with a 100% filling. Dilute with demineralised water to the recommended ratio.

Specifications

Chrysler MS 9176

Cummins 85T8-2

DAF 74002

Detroit Diesel

Ford WSS-M97B44-D

GM 6277M

John Deere H 24 B1 & C1

Mack 014GS 17004

MB 325.3

Leyland Trucks LTS 22 AF 10

Scania TB 1451

Volkswagen VW TL 774-F (G12 Plus)

Volvo VCS

Typicals

Density at 15 °C, kg/l 1,124

Flash Point PM, °C 115

pH - 33% in water 8,4

Reserve alkalinity, pH 5,6

Watercontents, mg/kg < 5000

Crystallizationpoint: 25 vol%, °C -12

Crystallizationpoint: 33 vol%, °C -22

Crystallizationpoint: 40 vol%, °C -27

Crystallizationpoint: 50 vol%, °C -40

Crystallizationpoint: 60 vol%, °C -56

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50671
1 L bottle50672
5 L can50548
20 L can50549
60 L drum50550
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.