

Product Information VM.10.20

30-01-2023

SynTruck Ultimate 10W-40

Description

SynTruck Ultimate 10W-40 is a 'Low-SAPS' lubricant with the following properties:

- Very powerful detergency, minimizing deposits in the hot zone of the engine
- Very strong dispersion that restricts the formation of particles to a minimum
- High and stable natural viscosity index
- Low sulphated ash, phosphor and sulphur content ('Low-SAPS')
- Powerful resistance against wear, resulting in strongly reduced wear of piston rings and cylinder-liners
- Lower fuel consumption

Application

SynTruck Ultimate 10W-40 is suitable for EGR engines with or without DPF(diesel particulate filter). This 'Low-SAPS' lubricant is recommended for Euro 4, Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. The product can be used under the toughest operating conditions all year round. Always check the product recommendation database for the right application.

Specifications

ACEA E6, E7, E9

API CK-4

Deutz DQC IV-18 LA

Mack EOS-4.5

MB 228.51

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

JASO DH-2

MAN M 3477 / M 3775

MB 228.52 / 228.31

MTU Type 3.1

DAF Extended Drain

Iveco 18-1804 TLS E9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,868
Viscosity -25 °C, mPa.s	6150
Viscosity 40 °C, mm ² /s	98,0
Viscosity 100 °C, mm ² /s	14,30
Viscosity Index	150
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	9,8
Sulphate Ash, %	0,98

Available packagings50691
20 L can50692
60 L drum50693
210 L drum