

Product Information 05.20.31

27-07-2024

Maestrol 2T Pro

Description

Maestrol 2T Pro is a 2-stroke (petrol) motor oil that is semi-synthetic. It is supplemented with special additives to achieve the following properties:

- Outstanding lubrication of all engine parts thanks to effective adhesion: wear is reduced and the service life of the engine is extended
- Powerful detergency, as a result of which the combustion chamber and the exhaust ports remain clear of deposits, even at high temperatures
- Almost complete combustion so that the spark plugs remain clean, ensuring optimal performance of the engine
- Excellent resistance to corrosion and wear
- Limited formation of smoke and odour
- Can also be mixed with unleaded petrol

Application

Maestrol 2T Pro semi-synthetic motor oil is suitable for high speed and heavy-duty, air-cooled 2-stroke engines in mopeds, motorcycles, scooters, chainsaws, lawnmowers, generators, etc. It is also suitable for 2-stroke engines with water cooling. Can be used as a self-mixing product, or in automatic lubrication systems. Mixing ratio: 1 part oil to 50 parts fuel or use the mixing ratio recommended by the manufacturer.

Specifications

API TC

JASO FD

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,866 |
| Viscosity 40 °C, mm ² /s | 38,70 |
| Viscosity 100 °C, mm ² /s | 7,10 |
| Viscosity Index | 147 |
| Flash Point COC, °C | 122 |
| Pour Point, °C | -45 |
| Total Base Number, mgKOH/g | 1,4 |

Available packagings



36260
1 L bottle



36456
5 L can



37540
15 L Bag in
Box



36733
20 L Bag in
Box



36457
20 L pail

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.