

Product Information PM.40.55 04-05-2024

N-Tech® Pro R+ Off Road 10W-40

Description

N-TECH® PRO R+ OFF ROAD 10W-40 is the most advanced, fully synthetic 4-stroke engine oil ever produced by Putoline Oil. Contains the unique N-TECH® additive system. N-TECH® PRO R+ OFF ROAD engine oil guarantees:

- Unsurpassed wet clutch performance and grip
- Extremely low wear for engine and transmission
- Minimal oil consumption
- ullet Excellent viscosity properties even at low temperatures, which significantly prevents wear on cold starts
- Excellent cleaning properties ensures long-term and optimum engine performance
- Excellent lubrication properties throughout the entire service life This fully synthetic 4-stroke motorcycle engine oil has been designed particularly for off road and competition motorcycles that perform under the most demanding conditions.

Application

Putoline Oil is a Dutch manufacturer and supplier of high quality oils and lubricants for motorcycles, scooters and quads only. This is what makes us unique. Almost 50 years of experience and continual research allows Putoline Oil to provide cutting edge products at the best price/quality ratio. Manufacturing our own products guarantees consistent high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API SN

JASO MA2

Typicals

Density at 15 °C, kg/l	0,854
Viscosity -25 °C, mPa.s	3520
Viscosity 40 °C, mm ² /s	85,00
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	164
Flash Point COC, °C	244
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,6
Sulphate Ash, %	0,85

Available packagings











74352 1 L bottle

74353 4 L can 74354 20 L Bag in Box

74356 60 L drum

74357 200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.