

Product Information PM.40.58

24-04-2024

N-Tech® SPR+ 5W-50

Description

N-TECH® SPR+ 5W-50 is a race proven, fully synthetic racing 4-stroke motorcycle oil based on an advanced mix of the best base oils available on the market. High ratio of PAO's (Polyalphaolefins) and synthetic esters ensure unrivalled quality and performance. The choice of the best base oils, in combination with the revolutionary N-TECH® additive system, improves power and minimises wear. SAE 5W-50 ensures a higher viscosity therefore a higher resistance to fuel dilution. Specially developed for extreme race conditions and starts. Combines maximum reliability with optimal wet clutch performance, increasing clutch grip and power.

Application

Putoline Oil is a Dutch manufacturer and supplier of high quality oils and lubricants for motorcycles, scooters and quads only. This is what makes us unique. Almost 50 years of experience and continual research allows Putoline to provide cutting edge products at the best price/quality ratio. Manufacturing our own products guarantees consistent high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Typicals

Density at 15 °C, kg/l	0,858
Viscosity -30 °C, mPa.s	6140
Viscosity 40 °C, mm²/s	108,00
Viscosity 100 °C, mm²/s	17,10
Viscosity Index	173
Flash Point COC, °C	234
Pour Point, °C	-45
Total Base Number, mgKOH/g	9,5
Sulphate Ash, %	1,19
HTHS, mPa.s	4,30
Noack, %	5,2

Available packagings



74405
1 L bottle



74407
20 L Bag in
Box

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.