

Product Information VC.10.03

29-01-2023

VatOil MultiCool LL12

Description

MultiCool LL 12 is a Long Life OAT (Organic Additives Technology) coolant. The product is based on monoethylene glycol and demineralised water. It is supplemented with additives to achieve the following properties:

- Excellent protection of all metals that are used in engines and cooling systems
- Does not affect seals, gaskets and hoses
- Very good resistance to foaming
- Nitrite, amine, phosphate and silicate-free
- Pink colour

Application

MultiCool LL 12 can be used throughout the year in the cooling systems of petrol and diesel engines. This organic Long Life coolant should be used undiluted and will then provide protection down to -38 °C.

Specifications

ASTM D3306/D4985/D6210

Chrysler MS 9176

Cummins 85T8-2

DAF 74002

Detroit Diesel

Ford WSS-M97B44-D

GM 6277M

John Deere H 24 B1 & C1

Mack 014GS 17004

MAN 324 Typ SNF

MB 326.3

Leyland Trucks LTS 22 AF 10

Renault 41-01-001/--S Type D

Volkswagen VW TL 774-F (G12 Plus)

Volvo VCS

Typicals

Density at 15 °C, kg/l	1,073
pH - value	8,5
Crystallizationpoint, °C	-38

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50696
1 L bottle50697
5 L can50545
20 L can50546
60 L drum50547
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.