

Product Information 07.10.17

05-12-2022

Universal Grease ST Q7

Description

ST Q7 Universal Grease is a green-coloured, universal, long-filament grease. It is formulated from a lithium soap thickening agent and a mineral base oil. Adding a small amount of polymers ensures extremely effective adhesion and an excellent, long-filament structure. Furthermore, it is supplemented with special anti-corrosion, anti-wear and 'Extreme Pressure' additives to achieve the following properties:

- Very strong adhesion to metal
- Superb resistance to water penetration
- Excellent mechanical stability
- Good resistance to corrosion and wear
- Excellent pumpability
- Outstanding EP properties

Application

ST Q7 Universal Grease is a green-coloured long-filament universal grease suitable for industrial, agricultural and forestry applications. Its outstanding adhesion makes it the first choice for slow to medium speed rotary applications. However, it is less suited to rapidly rotating bearings.

ST Q7 Universal Grease is available in a very handy, special Lube Shuttle screw cartridge. The Lube Shuttle grease guns can be ordered from us separately.

Specifications

NLGI Grade 2

DIN 51 502, KP 2 K-30

Typicals

Penetration (worked), 0,1 mm	280
Dropping Point, °C	190
Temperature Limits, °C	-30/130
Base oil Viscosity, 40 °C, mm ² /s	195,00
4-ball welding load, N	2600

Available packagings



33388

400 g Q-cartridge



33509

18 kg pail



33641

50 kg drum



33536

180 kg drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.