Product Information 01.20.10

12-10-2024

Bi-Turbo 15W-40

Description

Bi-Turbo 15W-40 is a universal, mineral motor oil based on premium solvent-refined base oils. It is supplemented with additives to achieve the following properties:

- Very powerful detergency and dispersion thereby preventing a high build-up of black sludge
- Very high resistance to oxidation
- Highly effective against wear
- Good resistance to corrosion and foaming
- A high and stable viscosity index
- A low tendency to evaporate
- No negative influence on catalytic converters

Application

Bi-Turbo 15W-40 is a universal mineral motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine or catalytic convertor. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

ACEA A3/B4
API SL/CF
MB 229.1
VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,879
Viscosity -20 °C, mPa.s	2800
Viscosity 40 °C, mm²/s	88,90
Viscosity 100 °C, mm²/s	13,50
Viscosity Index	135
Flash Point COC, °C	230
Pour Point, °C	-27
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,31

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

00215
1 L bottle

33078
4 L can

00328
5 L can

37487
15 L Bag in Box

32723
20 L Bag in Box

35049
20 L pail

10074
20 L can

10128
60 L drum

33713
200 L drum

10228
208 L drum

33544
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com