

Product Information 01.60.15

25-04-2024

Atlantic 4T 25W-40

Description

Atlantic 4T 25W-40 is a 4-stroke motor oil for outboard and inboard engines. Atlantic 4T 25W-40 is based on premium base oils, supplemented with special additives, which achieve the following properties:

- Lubrication of all engine parts
- Very powerful detergency, which ensures the engine is cleaner
- Good cold start properties
- Very high resistance to corrosion, oxidation and wear
- Outstanding shear stability

Application

Atlantic 4T 25W-40 is particularly suitable for use in high-speed, heavy-duty outboard and inboard motors. Because 4-stroke outboard motors place different requirements on motor oil, this oil is not suitable for use in cars.

Specifications

NMMA FC-W

Typicals

Density at 15 °C, kg/l	0,876
Viscosity -10 °C, mPa.s	6200
Viscosity 40 °C, mm ² /s	140,00
Viscosity 100 °C, mm ² /s	14,90
Viscosity Index	107
Flash Point COC, °C	242
Pour Point, °C	-27
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,79
Molybdenum, mg/kg	

Available packagings



33421
5 L can



33531
20 L pail



33530
60 L drum



33529
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.