

## Product Information VM.20.49

05-12-2021

### MonoFleet SHPD 60

#### Description

MonoFleet SHPD 60 is a universal engine oil. It is produced with high quality solvent refined base oils and a well-balanced choice of additives. MonoFleet SHPD 60 has the following properties:

- Excellent detergency preventing from deposits in the hot zones of the engine
- Very active dispersion, that prevents from deposits and sludge
- Powerful resistance against wear, corrosion and foam
- Low ash contents

#### Application

MonoFleet SHPD 60 is suitable for petrol and diesel engines, with or without supercharging, under all operating conditions. Always check the product recommendation database for the right application.

#### Specifications

ACEA E2

API SG/CF

MB 227.0/228.0

MAN 270

#### Typicals

Density at 15 °C, kg/l	0,899
Viscosity 40 °C, mm <sup>2</sup> /s	290,60
Viscosity 100 °C, mm <sup>2</sup> /s	23,50
Viscosity Index	101
Flash Point COC, °C	246
Pour Point, °C	-18
Total Base Number, mgKOH/g	6,9
Noack, %	3,3

#### Available packagings



50709  
5 L can



50710  
20 L can



50711  
60 L drum



50758  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.