

Product Information 08.20.13

27-07-2024

Compressol AS 68

Description

Compressol AS 68 is a high-grade, fully synthetic Long Life oil for oil-lubricated piston compressors. It is composed of specially selected, synthetic PAO base oils and advanced additives to achieve the following properties:

- Low oil consumption due to low volatility
- Highly stable against oxidation
- Excellent protection against corrosion
- Excellent anti-wear properties
- Excellent thermal stability
- A high viscosity index
- Good resistance to foaming
- Suitable for extended oil change intervals
- Prevents the formation of carbon deposits

Application

Compressol AS 68 is a high-grade, fully synthetic, Long Life compressor oil. Primarily intended for heavy-duty piston compressors with high final compression pressures and high final compression temperatures. The oil provides outstanding lubrication, even under the harshest conditions and at high operating temperatures.

Specifications

ISO 6743-3A DAJ

Typicals

Density at 15 °C, kg/l	0,835
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	10,60
Viscosity Index	148
Flash Point COC, °C	268
Pour Point, °C	-42

Available packagings



36554
20 L pail



37146
60 L drum



34496
200 L drum



37147
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.