

Product Information 01.40.85

21-02-2019

Elvado LSP 5W-30

Description

Elvado LSP 5W-30 is a modern, fuel-saving, synthetic motor oil, developed in accordance with the latest Low SAPS technologies for use in cars with particulate filters and/or catalytic converters. The special Low SAPS formula extends the service life. It is supplemented with specially selected, synthetic base oils and advanced additives to achieve the following properties:

- Fuel saving
- Reduced formation of combustion residues due to lower SAPS content
- Extended service life of particulate filters and catalytic converters
- A smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Elvado LSP 5W-30 is suitable for use in modern cars and vans with a particulate filter and/or catalytic converter. The special Low SAPS formula extends the service life. If the manufacturer so requires, extended oil change intervals are possible. Elvado LSP 5W-30 is highly suitable for use in the latest Mazda models equipped with a particulate filter. Furthermore, it is suitable for all other makes of car that require an ACEA C1 specification.

Specifications

ACEA C1

Jaguar Land Rover STJLR.03.5005

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -30 °C, mPa.s	3900
Viscosity 40 °C, mm ² /s	52,50
Viscosity 100 °C, mm ² /s	9,46
Viscosity Index	166
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	6,6
Sulphate Ash, %	0,45

Available packagings



33482
1 L bottle



33495
5 L can



33500
20 L pail



33501
60 L drum



33502
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.