

## Product Information 01.50.17

03-07-2024

### Agrisynth LSP Ultra 10W-40

#### Description

Agrisynth LSP Ultra 10W-40 motor oil is based on high-quality Low-SAPS additives in combination with specially selected base oils. Contributes to low exhaust gas emissions and low particulate emissions, thereby extending the lifespan of catalytic converters and particulate filters. Meets the requirements of both European and North American automotive manufacturers and has the following properties:

- Meets or exceeds the requirements of the current low emission standards
- Excellent cold start properties
- Very good shear stability
- Improved resistance to oxidation
- Excellent dispersive properties that keep deposits and sludge to a minimum
- Excellent properties against wear, corrosion and foaming

#### Application

Agrisynth LSP Ultra 10W-40 is suitable for the latest, high-speed 4-stroke diesel engines and can be used in Euro 5 and Euro 6 engines with SCR exhaust systems and in Euro 3 and Euro 4 engines, if required by the manufacturer.

#### Specifications

ACEA E6, E7, E8, E9, E11

API CK-4

Deutz DQC IV-18 LA

DTFR 15C110 (228.51)

Mack EOS-4.5

MB 228.51

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

DTFR 15C120 / 15C100

JASO DH-2

MAN M 3477 / M 3775

MB 228.51 / 228.52 / 228.31

MTU Type 3.1

DAF Extended Drain

Iveco 18-1804 TLS E9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,871
Viscosity -25 °C, mPa.s	6150
Viscosity 40 °C, mm <sup>2</sup> /s	98,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,30
Viscosity Index	150
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	9,8
Sulphate Ash, %	0,98

### Available packagings



36185  
5 L can



36186  
20 L pail



36593  
20 L can



36187  
60 L drum



36188  
208 L drum