



Product Information 02.35.36

04-02-2023

SP Matic 2072

Description

SP Matic 2072 is a synthetic Long Life ATF, specially developed for use in the latest generation of automatic DSG transmissions with dual-clutch technology. The unique formulation of SP Matic 2072 ensures that the product has the following properties:

- Excellent oxidation stability: extending the service life of the fluid
- Outstanding lubrication properties, even under the most extreme conditions
- Very high resistance to wear, corrosion and foaming
- Outstanding shear stability
- An extremely low pour point can be used at extremely low temperatures
- A very high viscosity index: reliable operation of the transmission at both high and low temperatures

Application

SP Matic 2072 has been specially developed for the new generation of High Tech DSG transmissions as used in a range of VAG models, along with an increasing number of models by other makes. Always consult the Kroon-Oil product advisory database for optimal use.

Specifications

BMW DCTF-1 / DCTF-1+ / LT-5

BorgWarner

Bugatti Veyron

Chrysler 68044345 EA & GA

Ferrari TF DCT-F3

Ford WSS-M2C936-A / WSS-M2C218-A1

Hyundai/Kia

MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21

Mitsubishi Dia-Queen SSTF-1

Porsche/ZF FFL-3

PSA 9734 S2

Renault EDC

Volvo 1161838 / 1161839

VW G 052 182 / G 052 529 / G 055 529

VW G 052 536 / G 055 536

Typicals

Density at 15 °C, kg/l	0,850
Viscosity 40 °C, mm ² /s	34,0
Viscosity 100 °C, mm ² /s	7,17
Viscosity Index	183
Flash Point COC, °C	201
Pour Point, °C	-48
Acid number, mgKOH/g	1,29

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings33481
1 L bottle35179
5 L can35479
15 L Bag in
Box32742
20 L Bag in
Box33491
20 L pail33638
60 L drum32664
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.